



Intel® RealSense™ D400 Series Calibration Tools and API

Release Notes

July 9, 2018

Version 2.6.4.0



INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

A "Mission Critical Application" is any application in which failure of the Intel Product could result, directly or indirectly, in personal injury or death. SHOULD YOU PURCHASE OR USE INTEL'S PRODUCTS FOR ANY SUCH MISSION CRITICAL APPLICATION, YOU SHALL INDEMNIFY AND HOLD INTEL AND ITS SUBSIDIARIES, SUBCONTRACTORS AND AFFILIATES, AND THE DIRECTORS, OFFICERS, AND EMPLOYEES OF EACH, HARMLESS AGAINST ALL CLAIMS COSTS, DAMAGES, AND EXPENSES AND REASONABLE ATTORNEYS' FEES ARISING OUT OF, DIRECTLY OR INDIRECTLY, ANY CLAIM OF PRODUCT LIABILITY, PERSONAL INJURY, OR DEATH ARISING IN ANY WAY OUT OF SUCH MISSION CRITICAL APPLICATION, WHETHER OR NOT INTEL OR ITS SUBCONTRACTOR WAS NEGLIGENT IN THE DESIGN, MANUFACTURE, OR WARNING OF THE INTEL PRODUCT OR ANY OF ITS PARTS.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined". Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or go to: <http://www.intel.com/design/literature.htm>.

Code names featured are used internally within Intel to identify products that are in development and not yet publicly announced for release. Customers, licensees and other third parties are not authorized by Intel to use code names in advertising, promotion or marketing of any product or services and any such use of Intel's internal code names is at the sole risk of the user.

Intel and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2018, Intel Corporation. All rights reserved.



Contents

1	What's New.....	5
	1.1 Release 2.6.4.0	5
	1.2 Release 2.5.2.0	5
2	Issues Resolved.....	6
3	Known Issues and Limitations	7
4	Installation and Additional Documentation	8



Revision History

Document Number	Revision Number	Description	Revision Date
	2.5.2.0	First Calibration Tools and API release	Jan 2018
	2.6.4.0	Support RGB calibration/ Updated kernel patching instructions for Linux	July 2018



1 What's New

1.1 Release 2.6.4.0

- Removed target-less mode from Dynamic Calibrator
- UI improvements
- New feature to calibrate RGB for accurate UV mapping on devices with RGB.
- Support Depth-RGB calibration on Intel® RealSense™ Depth Cameras D415 and D435.
- Improved on-screen instruction with embedded demo in Dynamic Calibrator for better user experience.
- Support devices that were previously recalibrated with OEM Calibration Tool for Intel® RealSense™ Technology versions 0.1.0, 0.2.0, 0.2.1, and 0.3.0.

1.2 Release 2.5.2.0

New Calibration Tool API product for Intel® RealSense™ D400 series 3D depth camera devices.

- Support Intel® RealSense™ Depth Module in the D400 series including D400, D410, D415, D420, D430, and D435
- Calibration with printed target
- Calibration with target displayed on iPhones and Android phones through Intel® RealSense™ Dynamic Target Tool app on Apple App Store and Google Play
- Calibration without target
- Support Calibration API with Intel proprietary algorithms and user custom algorithms
- Support calibration parameter read/write/restore
- Includes source code for sample calibrator application with Intel proprietary algorithms
- Includes source code for custom calibration sample app with OpenCV algorithm and white paper demonstrate how to calibrate with user custom algorithms
- Support Windows and Linux



2 Issues Resolved

This section lists issues resolved in this release:

Issue	Description
DSO-7965 Restore data from Gold sector to Dynamic sector not working on D435 devices with 5.8.15.0 and older firmware	The issue is fixed in newer firmware. Please use FW 5.9.8.0 and later while running dynamic calibration or the -g option in CustomRW tool.



3 Known Issues and Limitations

This section lists known product limitations.

Issue	Description
DSO-2592	Impact of reflections from environment lighting <ul style="list-style-type: none"> Lighting reflection on phone screens severe impacts targeted calibration effectiveness. When a phone target is used where lighting reflection on phone glass screen presents, for example, outdoor under bright sunlight, or indoor with lots of lights surrounded, calibration performance degrade. In severe cases, calibration may not converge (as the impacted images thrown away) and it takes longer to complete or no result may be reached. In case this issue happens, try to move the phone to another location or a different direction to avoid reflections.
DSO-4182	Impact of rolling wave bands in images with AWG devices and phone targets on Samsung displays <ul style="list-style-type: none"> Images from AWG devices and phone targets on Samsung displays have rolling wave bands, and in some cases this would affect effectiveness of calibration since its algorithm looking for accurate patterns in target. Only AWG devices impacted. ASR/PSR no impact. Only AOS Samsung target phones impacted. IOS phones no impact. Impact should be limited to performance. Accuracy should not be impacted based on existing tests. The issue was worked around in dynamic calibration by automatically adjust auto exposure brightness to minimize the impact from the wave bands.
DSO-5731	Target on Galaxy S5 phone not accurate. Avoid use this phone as target.
DSO-9276	Hot plug doesn't work on Win10 RS3 with LibRealSense



4 *Installation and Additional Documentation*

For installation and other information, please refer to the User's Guide and Programmer Guide available online:

- Intel® RealSense™ D400 Series Calibration Tools User Guide
- Intel® RealSense™ D400 Series Calibration Tools API Programmers Guide