

Release Note NCI Proximity Driver over Intel ME

Document information

Info	Content
Author	Hariom Kesh
Author Role	Developer
Keywords	NXP Intel Proximity Driver Intel Management Engine Interface
Abstract	

NXP

Revision History

Revision	Date	Description	Author
V7.7.6	2015/08/03		Hariom Kesh

Contents

- Contents3**
- 1. **Document purpose4**
- 2. **Installation instructions.....4**
- 3. **Material list4**
- 4. **Scope4**
- 5. **Binaries details.....4**
- 6. **Test Information4**
- 7. **Know issues and restrictions4**
- 8. **PR/CR/IR Details.....5**
- 9. **Appendix.....6**
 - 9.1 Installer's switches6
 - 9.2 Radio and Power status6

1. Document purpose

This document is the release note of NCI Proximity Driver. This document will describe content of the delivery and how to use installer.

2. Installation instructions

If the driver is provided as a silent installer, simply launch the setup.exe and the driver installation process should start. If the installer is not silent, a GUI should appear and let user proceed the installation. The installer can take several command line parameters:

/S : The installer will be silent if it's a non silent installer.

The installer may support additional switches, please have look in the related chapter in this document.

3. Material list

This package contains the following files:

- ***NXP_ProximityDriver_Release_note.pdf*** : this document
- ***setup.exe*** : installer for Proximity Driver.
- ***driver_binaries/*** : Binaries for Proximity Driver x86 & x64 for Windows10
- ***pdb/*** : All pdb files for Proximity Driver for Windows10

4. Scope

- This package is Win10 (x64 & x86) HLK certified and targeted for Win10 OS only.

5. Binaries details

- Proximity Driver : 7.7.6.0
- Firmware version
 - NPC 100 : 8.2.3
 - NPC 300 : 10.1.11
- PCSC Driver : 1.0.4.39
- GPIO Driver : 1.0.3.0

6. Test Information

- OS : Win10 EEAP build : 10240
- Platform : Intel Skylake
- NFC module : NPC100 & NPC300
- ME : 11.0.0.1122

7. Know issues and restrictions

- Cannot test secure key

NXP

8. PR/CR/IR Details

- PR/CR/IR Solved in this release
 - o SC52903: [NPC100, Win10, NFC ON/OFF, reboot] NEC

9. Appendix

9.1 Installer's switches

The driver installer support the following switches:

```
setup.exe [/SD] [/LOG=path] [/X=path] /RFOFF /WIZARD /ACCEPTLICENSE
```

Note : A valid path is an absolute path with the following format :

- PATH_WITH_NO_SPACES
- "PATH_WITH_NO_SPACES"
- "PATH WITH SPACES"

Options :

/SD : Completely silent mode.

This option disables all the message boxes, no notification will appear, even on error.

/LOG : Log file.

By default, a log file named "install_log.txt" is created in the installation directory.

If this option is used, the log file name used is the complete path. The log file contains the following information :

- The time when the application has been launched
- The state of the silent mode (ON or OFF)
- The confirmation of extraction of the driver in the path precised if /X option has been used
- If an error occurs, a description of this error
- The final status of the installation, and the time when the application stopped.

/X : Extract driver binaries to specified path without installing anything else.

/DX : Extract driver following MUP specification.

/RFOFF : The radio does not polling after installing the driver.

/WIZARD : Enable Installer WIZARD for silent installer. /SD override this switch.

/S : Enable silent mode. Popup are still displayed if an error occurs.

/ACCEPTLICENSE : When using /S or /SD, this switch silently accept license.

/CONFIGXTAL : Force crystal configuration.

9.2 Radio and Power status.

This table indicates the Radio status, Power status (Ven) and libnfc status depending on platform state.

Transition	Ven status	Radio status	LibNfc status
Boot	Toggled OFF/ON	Polling ON	initialized
SX/CS/BOOT => S0	Toggled OFF/ON	Polling ON	initialized
S0 => S1 (Screen Off)	Ven OFF	Polling OFF	deinitialized
S0 => S3	Ven OFF	Polling OFF	deinitialized
S0 => S4	Ven OFF	Polling OFF	deinitialized
S0 => S5	Ven OFF	Polling OFF	deinitialized
S0 => CS	Ven OFF	Polling OFF	deinitialized
Driver enabled	Toggled OFF/ON	Polling ON	initialized
Driver disabled	Ven OFF	Polling OFF	deinitialized
Air plane mode ON / NFC Off	Ven OFF	Polling OFF	deinitialized
Air plane mode OFF / NFC On	Toggled OFF/ON	Polling ON	initialized